

**CLAIMS**

Sub  
a1

1 1. A roof structure comprising:  
2 (22)  
3 a support web;  
4 (24)  
5 an exposure surface perpendicularly bisecting the  
6 support web;  
7 (50)  
8 a collector perpendicularly bisecting the support web  
opposite the exposure surface, wherein the collector has flanges projecting  
outward in opposing lateral directions, each flange having a distal edge  
upwardly extending from the flange.

1 2. The roof structure of claim 1, wherein the exposure surface and  
2 the collector are integral with the support web to eliminate the necessity for  
3 parts inventory.

1 3. The roof structure of claim 2, wherein the distal edge upwardly  
2 extends from each flange at an angle of about 90 to 175 degrees.

1 4. The roof structure of claim 2, wherein the distal edge upwardly  
2 extends from each flange at an angle of about 125 to 145 degrees.

1 5. The roof structure of claim 2, wherein the exposure surface has  
2 a negative angle to the support web.

1 6. The roof structure of claim 2, wherein the collector has a depth  
2 greater than the maximum expected deflection of the roof support.

1 7. The roof structure of claim 2, wherein the distal edge is general  
2 parallel to the support web.

1 8. The roof structure of claim 2, wherein the roof structure is  
2 manufactured by a pultrusion process, extrusion process, weldment process,  
3 rollform process, or a combination thereof.

1 9. A roof panel and roof structure combination comprising:  
2 (14)  
at least one roof panel including;

401501001

Sub  
a2

3 an exterior surface; and  
4 an interior surface; and  
5 a roof structure including:  
6 an exposure surface;  
7 a collector including opposing lateral distal edges  
8 that upwardly extend from the collector; and  
9 a support web integral with and perpendicularly  
10 bisecting the exposure surface and the collector, wherein the exposure  
11 surface is opposite the collector; and  
12 wherein the roof panel is closely adjacent to the support  
13 web, and the distal edges of the collector supports the roof panel.

1 (1b) 10. The combination of claim 9, wherein the roof panel includes a  
2 drip edge extending longitudinally along the interior surface of the roof panel.

1 11. The combination of claim 10, wherein the drip edge extends  
2 parallel with the longitudinal axis of the roof support.

1 12. The combination of claim 9, wherein a first roof panel and a  
2 second roof panel abut opposing sides of the support web, and the exposure  
3 surface of the roof support overlaps the exterior surface of both the first  
4 panel and the second panel.

1 13. The combination of claim 9, wherein the exposure surface of  
2 the roof support includes flanges projecting outward in opposing lateral  
3 directions.

1 14. The combination of claim 13, wherein the exterior surface of  
2 the roof panel includes an arcuate projection and at least one flange of the  
3 exposure surface of the roof support includes an arcuate channel, the arcuate  
4 channel being configured to interface with the arcuate projection of the roof  
5 panel.

1 15. The combination of claim 14, wherein the arcuate channel  
2 extends parallel to the longitudinal axis of the roof support.

A2  
cont

20370" 505000

Sub  
a3

Sub  
a.4

1 16. The combination of claim 9, wherein the roof structure has a  
2 modulus of elasticity of at least about 2,500,000 pounds per square inch.

1 17. The combination of claim 9, wherein the opposing lateral distal  
2 edges of the collector upwardly extend at an angle from the collector of  
3 about 90 to 175 degrees.

class  
264/219

1 18. A method of making a roof support comprising:  
2 introducing fibers to a resin bath to form a fiber-resin  
3 combination;  
4 contouring the fiber-resin combination in the shape of a  
5 roof support; and  
6 curing the resin-fiber combination.

1 19. The method of claim 18, wherein the fibers are selected from a  
2 group consisting of at least glass, graphite, polyethylene, polyvinyl and a  
3 combination of the same.

1 20. The method of claim 18, wherein the resin includes an epoxy  
2 resin.

1 21. The method of claim 18, wherein the fiber-resin combination is  
2 contoured in the shape of a roof support including:

3 a support web;  
4 an exposure surface perpendicularly bisecting the  
5 support web;  
6 a collector perpendicularly bisecting the support web  
7 opposite the exposure surface, wherein the collector has flanges projecting  
8 outward in opposing lateral directions, each flange having a distal edge  
9 parallel to the support web and upwardly extending from the flange.

1 22. The method of claim 18, further comprising cutting the cured  
2 fiber-resin combination.

2007-05-04 10:00

1           23.    The method of claim 18, wherein the roof support has a  
2   moment of inertia of about 3.180 inches<sup>4</sup>.

1           24.    The method of claim 18, wherein the fiber-resin combination is  
2   in the shape of a roof support including a support web having a top surface  
3   and a bottom surface, wherein the top surface is configured to be closely  
4   adjacent to an interior surface of a roof panel.

ALL  
a5

2025-05-20 10:50:00